



Cat[®] 988K

Wheel Loader

The Cat[®] 988K Wheel Loader helps you move more material in less time, at a lower cost per ton, for a faster return on your investment. This machine offers significant fuel savings with durability to achieve multiple life cycles.

Proven Reliability

- Cat C18 engine is built and tested to meet your most demanding applications.
- Achieves longer engine life and improved fuel efficiency with reduced rated speed.
- Cat torque converter with lock-up clutch eliminates torque converter losses and lowers system heat.
- Maximum responsiveness with Steering and Integrated Control (STIC[™]).
- Moves more material more efficiently with improved power and control.
- Durable construction withstands the toughest loading conditions and multiple life cycles.

Durability

- Best-in-class transmission for long life and consistent, smooth shifting; specifically designed for mining applications.
- Advanced Productivity Electronic Control Shifting (APECS) transmission controls for greater momentum on grades.
- Positive Flow Control (PFC) hydraulic system increases efficiency, bucket feel, and responsiveness with consistent performance.
- Advanced filtration system for extended performance and reliability of the hydraulic system.
- Impeller Clutch Torque Converter (ICTC) minimizes tire spin by allowing torque to adjust to underfoot conditions.

Achieve Greater Productivity

- Superior digging, higher bucket fill factors, reduced dig times.
- Improved visibility over the top of the linkage.
- Up to 10% more payload per pass, higher efficiency, and improved pass match.
- Operators can now check tire pressure during operation with any change sending a fault code to VisionLink[®], preventing premature tire failure.
- In-truck loading applications.
- Convenient, responsive, electro-hydraulic controls increase operator productivity.
- Integrated steering and transmission controls.

Superior Fuel Efficiency

- Up to 20% less fuel consumption.
- Economy Mode for reduced rated engine speed and reduced fuel consumption.
- Flow sharing hydraulics for full flow at reduced engine rpm.
- Fully integrated electronic engine controls make your fuel go farther.
- Engine Idle Shutdown for less fuel used while idling.
- Increased hydraulic speed and faster cycle times for decreased idle, decreased fuel burn, and increased efficiency.

Three engine emission options are available:

1. Meets U.S. EPA Tier 4 Final, EU Stage V, and Japan 2014 emission standards.
2. Meets Brazil MAR-1 and China Nonroad Stage III emission standards, equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
3. U.S. EPA Tier 2 and EU Stage II equivalent.



Cat® 988K Wheel Loader

Increase Productivity and Efficiency with Integrated Technologies

- Cat Technologies developed to monitor, manage, and enhance your jobsite operations.
- Cat Payload provides accurate weighing* of the materials you are loading and hauling. Payload data is displayed in real-time to improve productivity and reduce overloading.
- Cat Detect enhances awareness of the environment around working equipment and provides alerts to help keep people and assets safe on the jobsite.
- Product Link™ wirelessly connects you to your equipment, giving you access to essential information you need to know to run your business.
- Gain valuable insight into how your machine or fleet is performing.
- Optional Advanced Productivity subscription provides comprehensive actionable information to help you manage and improve the productivity and profitability of your operations.

Safety Features

- Achieve precise positioning for easy loading in tight areas with 43 degrees of steering articulation.
- Precise machine control by load-sensing hydraulic steering system.
- Reduced stairway angles and standard stairway lighting provide reduced risk of slips, trips and falls due to better visibility of the steps and stairway.
- Left- and right-hand stairs with 45-degree angle.
- Computerized monitoring system with warning indicators.
- Standard Cat Vision enhances visibility behind the machine, helping you work safely and confidently.
- Pressurized cabin with filtered air and reduced sound levels.

Reduced Maintenance Time and Costs

- 10% lower maintenance costs.
- Grouped service points provide easy access to critical daily service checks.
- Electro-hydraulic controls.
- Swing-out engine compartment service doors.
- Reduced waste with maintenance-free batteries.
- Ecology drains to prevent spilled contaminants and allow for easier service.
- Vehicle Information Management System (VIMS™) notifications to resolve problems before failure.
- Ground level access to transmission control valves.
- Longer life, rebuildability, and high resale value.

Easy, Comfortable Operator Environment

- Best-in-class operator comfort and ergonomics.
- Comfort Series III seats with extra thick, contoured cushions provide total comfort throughout the workday.
- Easy-to-reach levers and seat-mounted implement pod to reduce fatigue.
- Ergonomic switch placement and displays with large, backlit switches and LED indicators.
- Two-position rocker switch activates the electro hydraulic parking brake.
- Reduced vibrations from isolated cab mounts and seat air suspension.
- Automatic cab temperature controls.

**Not legal for trade.*

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
ELECTRICAL			POWER TRAIN (CONTINUED)		
Alarm, back-up	✓		Cat Production Measurement ready	✓	
Alternator, single 150 amp	✓		Crankcase guard	✓	
Converter, 10/15 amp, 24V to 12V	✓		Electro hydraulic parking brake	✓	
Lighting system (halogen, work lights, access and service platform lighting)	✓		Engine block heater 120V or 240V		✓
Starting and charging system, 24V	✓		Engine, C18 MEUI™ diesel, turbocharged/aftercooled	✓	
Starter emergency start receptacle	✓		Engine oil change system, high speed, Wiggins		✓
Starter lockout in bumper	✓		Ground level engine shutoff	✓	
Transmission lockout in bumper	✓		High ambient cooling – software		✓
OPERATOR ENVIRONMENT			Turbine precleaner, engine air intake	✓	
Air conditioner	✓		Radiator, Aluminum Modular Radiator (AMR)	✓	
Cab precleaner		✓	Starting aid, ether, automatic	✓	
Cab, sound suppressed and pressurized, integrated rollover protective structure (ROPS/FOPS) radio ready for entertainment, includes antenna, speakers and converter (12-volt 5-amp) and power port	✓		Throttle lock, electronic	✓	
Cat Detect, object detection system		✓	Torque converter, Impeller Clutch (ICTC) with Lock Up Clutch (LUC), Rimpull Control System	✓	
Cat Vision, rear vision camera system	✓		Transmission, planetary powershift, 4F/3R electronic control	✓	
Heater, defroster	✓		Manual switch and automatic fuel priming	✓	
Horn, electric	✓		ADDITIONAL EQUIPMENT		
LED warning strobe		✓	Aggregate handler		✓
Light, directional	✓		Automatic bucket lift kickout/positioner	✓	
Lights, HID or LED		✓	Base machine price includes a rim allowance	✓	
Lunchbox, beverage holders	✓		Block Handler		✓
Mirrors, heated		✓	Cat Clean Emission Module (CEM)	✓	
Mirrors, rearview (externally mounted)	✓		Cold weather starting (extra starter plus two batteries)		✓
Radio, AM/FM/CD/MP3		✓	Doors, service access (locking)	✓	
Bluetooth® with Satellite Sirius			Ecology drains for engine, radiator, hydraulic tank	✓	
Radio, CB ready		✓	Fast fill fuel system (Shaw-Aero)		✓
Rimpull Control System (RCS)	✓		Front and rear roading fenders		✓
Seat, Cat Comfort Series III, heated and ventilated, air suspension, six-way adjustable	✓		Hitch, drawbar with pin	✓	
Seat belt minder	✓		Hydraulic, steering and brake filtration/screening system	✓	
Seat belt, retractable, 76 mm (3 in) wide	✓		Hydraulically driven demand fan	✓	
STIC System	✓		Load and carry counterweight		✓
UV glass	✓		Millyard		✓
Wet-arm wipers/washers (front and rear) – intermittent front and rear wipers	✓		Oil sampling valves	✓	
Window pull-down visor		✓	Premixed 50% concentration of extended life coolant with freeze protection to -34° C (-29° F)	✓	
POWER TRAIN			Rear access to cab and service platform	✓	
Antifreeze -50° C (-58° F)		✓	Steel Mill		✓
Brakes, oil-cooled, multi-disc, service/secondary	✓		Steering, load sensing	✓	
Case drain screens	✓		Tire Pressure Monitoring System		✓
Cat Production Measurement		✓	Toe kicks	✓	
			Vandalism protection caplocks	✓	

Cat® 988K Wheel Loader

Technical Specifications

Engine		
Engine Model	C18	
Rated Speed	1,700 rpm	
Peak Power Speed	1,500 rpm	
Engine – ISO 14396:2002	432 kW	580 hp
Gross – SAE J1995:2014	439 kW	588 hp
Net Power – SAE J1349:2011	401 kW	541 hp
Bore	145 mm	5.7 in
Stroke	183 mm	7.2 in
Displacement	18.1 L	1,105 in ³
Peak Torque @ 1,200 rpm	3023 N·m	2,230 lb-ft
Torque Rise	58%	

Three engine emission options are available:

1. Meets U.S. EPA Tier 4 Final, EU Stage V, and Japan 2014 emission standards.
2. Meets Brazil MAR-1 and China Nonroad Stage III emission standards, equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
3. U.S. EPA Tier 2 and EU Stage II equivalent.

Operating Specifications		
Operating Weight	51 062 kg	112,574 lb
Rated Payload – Quarry Face	11.3 tonnes	12.5 tons
Rated Payload – Loose Material	14.5 tonnes	16 tons
Bucket Capacity Range	4.7-13 m ³	6.2-17 yd ³
Cat Truck Match – Standard	770-772	
Cat Truck Match – High Lift	773-775	

Transmission					
Transmission Type			Cat planetary power shift		
Speed	km/h	mph	Speed	km/h	mph
Forward 1	6.5	4.0	Direct Drive Forward 1	Lock-up disabled	
Forward 2	11.6	7.2	Direct Drive Forward 2	12.5	7.8
Forward 3	20.4	12.7	Direct Drive Forward 3	22.3	13.9
Forward 4	34.7	21.6	Direct Drive Forward 4	39.3	24.4
Reverse 1	7.5	4.7	Direct Drive Reverse 1	8.0	5.0
Reverse 2	13.3	8.3	Direct Drive Reverse 2	14.3	8.9
Reverse 3	23.2	14.4	Direct Drive Reverse 3	25.5	15.8

• Travel speeds based on 35/65-R33 tires.

Hydraulic System – Lift/Tilt		
Lift/Tilt System – Circuit	EH – Positive Flow Control, Flow Sharing	
Lift/Tilt System	Variable Displacement Piston	
Relief Valve Setting – Lift/Tilt	32 800 kPa	4,757 psi

Hydraulic Cycle Time (1,400-1,860 rpm)	
Rackback	4.5 Seconds
Raise	8.0 Seconds
Dump	2.2 Seconds
Lower Float Down	3.5 Seconds
Total Hydraulic Cycle Time (empty bucket)	18.2 Seconds

Hydraulic System – Steering		
Steering System – Circuit	Pilot, load sensing	
Steering System – Pump	Piston, variable displacement	
Relief Valve Setting – Steering	30 000 kPa	4,351 psi
Total Steering Angle	86°	
Steering Cycle Time (high idle)	3.4 Seconds	
Steering Cycle Time (low idle)	5.6 Seconds	
Steering	ISO 5010:2007	

Service Refill Capacities		
Fuel Tank	712 L	188 gal
Diesel Exhaust Fluid Tank (for Tier 4 Final/Stage V only)	33 L	8.7 gal

- All non-road Tier 4 Final/Stage V diesel engines are required to use:
 - Ultra Low Sulfur Diesel (ULSD) fuels containing 15 ppm (mg/kg) sulfur or less.
 - For Tier 4 engines: Cat engines are compatible with the following renewable, alternative, and bio-fuels* with lower greenhouse gas emission impact:
 - Up to B20 biodiesel (FAME) **
 - Up to 100% HVO and GTL renewable fuels
 - * Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendations” (SEBU6250) for details.
 - **B30, where mandated can be used. For use of higher blends, up to B100, consult your Cat dealer.
 - For pre-Tier 4 engines: Cat engines are compatible with the following renewable, alternative, and bio-fuels* with lower greenhouse gas emission impact:
 - Up to B20 biodiesel (FAME) **
 - Up to 100% HVO and GTL renewable fuels
 - * Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendations” (SEBU6250) for details.
 - ** Engines with aftertreatment devices can use up to B20. Engines with no aftertreatment devices can use higher blends, up to B100.
 - Cat DEO-ULS™ or oils that meet the Cat ECF-3, API CJ-4, and ACEA E9 specifications are required.
 - Only use DEF that meets ISO 22241-1 standards.

Air Conditioning System	
The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1.8 kg of refrigerant which has a CO ₂ equivalent of 2.574 metric tonnes.	

Sound Performance – Tier 4 Final/Stage V		
	Standard	Suppression
Operator Sound Level (ISO 6396:2008)	72 dB(A)	72 dB(A)
Machine Sound Level (ISO 6395:2008)	111 dB(A)	109 dB(A)

Sound Performance – Tier 2/Stage II Equivalent, Tier 3/Stage IIIA Equivalent		
	Standard	Suppression
Operator Sound Level (ISO 6396:2008)	73 dB(A)	72 dB(A)
Machine Sound Level (ISO 6395:2008)	112 dB(A)	110 dB(A)

- The operator sound pressure level was measured according to the test procedures and conditions specified in ISO 6396:2008. The measurement was conducted at 70 percent of the maximum engine cooling fan speed.
- Hearing protection may be needed when the machine is operated with a cab that is not properly maintained or when the doors or windows are open for extended periods or in a noisy environment.
- The machine sound power level was measured according to the test procedures and conditions specified in ISO 6395:2008. The measurement was conducted at 70 percent of the maximum engine cooling fan speed..



オフロード法2014年
基準適合

AEXQ2592-01 (10-2021)
Global

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com. Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options. © 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Product Link, VIMS, STIC, MEUI, DEO-ULS, “Caterpillar Corporate Yellow”, the “Power Edge” and Cat “Modern Hex” trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

